

Havis docking stations take the complexity out of going digital in work trucks, waste management vehicles, warehouse forklifts, and more. You get everything you need in an all-in-one solution with docking, electronics, communication ports and power.

#### The Complete Docking Solution

- Fits 8" and 10" Zebra ET4x tablets w/rugged frame
- Height-adjustable rugged military-grade design
- Standard or advanced I/O port replication
- Power supply options include external AC and internal DC (isolated or non-isolated)
- Built-in LED power indicator for easy diagnostics
- Integrated VESA 75 mounting pattern for easy attachment
- Spring-loaded floating connector head for constant contact

#### **Easy Usability With Custom Flexibility**

- · Easy one-handed docking/undocking
- Compact and lightweight design for easy tablet access
- Easy access to buttons, ports and scanner when docked
- Rounded edges for user comfort and safety
- Keyed lock to deter theft and ensure peace of mind
- Compatible with attachable hand and shoulder straps





**Dimensions:** 8.3" H (21.1 cm) x 8.6" W (21.9 cm) x 2.9" D (7.4 cm)

Certifications: CE Certified, UKCA and RoHS Compliant, UL Listed (Pending)

Vibration Testing: MIL-STD 810H 514.5

Impact Test: Crash Simulation per SAE J1455 30mph

Cycle Test: Latch Tested 30,000 cycles

Environmental Testing: Hot/Cold Operation & Storage

Product Weight: 1.86 lbs. (0.85 kg)

Standard Port Replication: USB2.0 (1); power input

Advanced Port Replication: USB2.0 (2); Ethernet (1); Powered Serial

(1 @ 5V); power input

Input Voltage Range: 9-36V (non-isolated) or 18-75 (isolated)

## 8" Configuration

**Dimensions:** 7.2"H (18.3cm) x 8.6"W (21.9cm) x 2.9"D (7.4 cm)

Certifications: CE Certified, UKCA and RoHS Compliant, UL Listed (Pending)

Vibration Testing: MIL-STD 810H 514.5

Impact Test: Crash Simulation per SAE J1455 30mph

Cycle Test: Latch Tested 30,000 cycles

Environmental Testing: Hot/Cold Operation & Storage

Product Weight: 1.86 lbs (0.85 kg)

Standard Port Replication: USB2.0 (1); power input

Advanced Port Replication: USB2.0 (2); Ethernet (1); Powered Serial

(1 @ 5V); power input

Input Voltage Range: 9-36V (non-isolated) or 18-75 (isolated)





www.havis.com

## Connect with Havis for More Information.

Havis Zebra Tablet Mounts | 1.800.524.9900 | sales@havis.com

ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©2023 Zebra Technologies Corp. and/or its affiliates.

# Havis: Productivity in Motion

For over 80 years, Havis has been a trusted designer and manufacturer of rugged in-vehicle mobile office solutions. We partner with leading automotive and mobile technology manufacturers as well as software developers to develop custom and proven docking solutions to fit real-world applications. With U.S.based manufacturing including steel and injection molding, we produce solutions for retail & hospitality, public safety, energy & utilities, warehouse & distribution, transportation & logistics, and other demanding environments.

