HAVIS DOCKING STATIONS FOR DELL 12" LATITUDE 7230 RUGGED EXTREME TABLET

DS-DELL-900 SERIES



ENABLING TECHNOLOGY IN PUBLIC SAFETY

- Optional port replication with Advanced or Standard content
- Side-mounted USB 3.0 port
- LED power indicator
- Optional quad pass-thru antenna connection
- One-handed docking & undocking
- Spring-loaded connector head
- Options for internal or external power supplies available
- Access to all tablet buttons & ports when docked
- Compatible with Dell 7230 tablet accessories including hard & soft handles, magnetic mount, rotating hand strap & shoulder strap
- Compact & lightweight
- Integrated cable management system
- Integrated VESA 75 mounting pattern

HAVIS DOCKING STATIONS FOR DELL 12" LATITUDE 7230 RUGGED EXTREME TABLET

DS-DELL-900 SERIES



DELL 7230 TABLET SOLUTION

- Compact design with one-handed docking & undocking
- Advanced or basic port replication (optional)
- Quad pass-thru antenna connection (optional)
- Non-isolated internal or external power supply (optional)
- LED power indicator

PART NUMBER	ETHERNET	USB-C	USB 3.0	HDMI	POWERED SERIAL	POWER INPUT	PASS-THRU ANT	ANT TYPE	EXT POWER	INT POWER
DS-DELL-901	1	1 REAR	2 REAR 1 SIDE		1 @ 5V	9-36V				NON-ISO
DS-DELL-901-4	1	1 REAR	2 REAR 1 SIDE		1 @ 5V	9-36V	QUAD	SMA		NON-ISO
DS-DELL-902	1	1 REAR	2 REAR 1 SIDE	1	1 @ 5V	9-36V				NON-ISO
DS-DELL-902-4	1	1 REAR	2 REAR 1 SIDE	1	1 @ 5V	9-36V	QUAD	SMA		NON-ISO
DS-DELL-903										
DS-DELL-903-4							QUAD	SMA		
DS-DELL-904	1	1 REAR	2 REAR 1 SIDE		1 @ 5V	19.5V*				
DS-DELL-904-4	1	1 REAR	2 REAR 1 SIDE		1 @ 5V	19.5V*	QUAD	SMA		
DS-DELL-907	1	1 REAR	2 REAR 1 SIDE	1	1 @ 5V	19.5V*				
DS-DELL-907-4	1	1 REAR	2 REAR 1 SIDE	1	1 @ 5V	19.5V*	QUAD	SMA		

*Requires an external Havis-approved DC power supply

SPECIFICATIONS:

Height: 10.2-in (25.9 cm)
Width: 10-in (25.4 cm)
Depth: 3.5-in (8.9 cm)
Weight: 2.75 lbs (1.25 kg)

CERTIFICATIONS & TESTING:

UL Safety (pending)
CE Certified; RoHS Compliant
Vibration Testing: MIL-STD 810H 514.8
Impact Test: SAE J1455 30mph Crash Testing
Cycle Test: Latch Handle & Docking Connector Connectors Mechanism 30,000 cycles
Environmental Testing: Hot/Cold Operational & Storage